

DOME CAMERA



Model	RNDE-B301A	LNV5460R	LNV7260R		
Camera	Image Sensor	CMOS	CMOS	CMOS	
	Lens	4mm fixed Lens	3.3-10mm, Motorized Lens	3.3-10mm, Motorized Lens	
	Min. Illumination	Color 0.05 lux @ F1.4 (AGC ON), B/W 0 lux @ IR LED on	Color 0.5 lux @ F1.4 (AGC ON), B/W 0 lux @ IR LED on	Color 0.03 lux @ F1.4 (AGC ON), B/W 0 lux @ IR LED on	
	Day / Night	Dual ICR	Dual ICR	Dual ICR	
	WDR	Digital WDR	Digital WDR	Digital WDR	
	IR LEDs	8	32	32	
	IR Distance	20 m	30 m	30 m	
	Image Setting	Configurable Brightness, Saturation, Contrast, HLC, Smart Defog, corridor	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS	
Video/Audio	Video Compression	H.265, H.264 HP / MP / BP, M-JPEG	H.265, H.264 HP / MP / BP, M-JPEG	H.265, H.264 HP / MP / BP, M-JPEG	
	Resolution	60Hz: 1080p@30fps, 960p@30fps, 720p@60fps 50Hz: 1080p@25fps, 960p@25fps, 720p@50fps	60Hz: 1440p@25fps, QXGA@25fps, 1080p@30fps, 960p@30fps, 720p@30fps 50Hz: 1440p@25fps, QXGA@25fps, 1080p@25fps, 960p@25fps, 720p@25fps	60Hz: 1080p@30fps, 960p@30fps, 720p@60fps 50Hz: 1080p@25fps, 960p@25fps, 720p@50fps	
	Max. Frame Rate	30fps@1920x1080, 60fps@1280x720	25fps@2560x1440, 30fps@1920x1080	30fps@1920x1080, 60fps@1280x720	
	Multi-Streaming	3	3	3	
	ROI (Region of Interest)	4 zones	3	8	
	Privacy Mask	Yes (Up to 4)	Yes (Up to 4)	Yes (Up to 4)	
	Motion Detection	Yes	Yes	Yes	
	Video Analytics	Tripwire / Perimeter / Missing object / Crowd / Loitering / Fast Moving / Parking	Tripwire / Perimeter / Missing & Foreign object / Crowd / Loitering / Fast Moving / Parking / Audio Offline	Tripwire / Perimeter / Missing & Foreign object / Crowd / Loitering / Fast Moving / Parking / Audio Offline	
	Streaming on Motion / Text Overlay	Yes / Yes	Yes / Yes	Yes / Yes	
	Audio Compression	G.711A / G.711U / ADPCM / AAC	G.711A / G.711U / ADPCM/AAC	G.711A / G.711U / ADPCM / AAC	
	Two-way Audio	-	Yes	Yes	
	Audio Detection	Yes	Yes	Yes	
	Event	Event Trigger	Motion Detection / IP Conflict / Port Alarm	Motion Detection / IP Conflict / MAC Conflict / Port Alarm	Motion Detection / IP Conflict / MAC Conflict / Port Alarm
		Event Notification	Email, FTP	Relay out, Email, FTP	Relay out, Email, FTP
Pre/Post Event Buffering		Yes	Yes	Yes	
Interface	Analog Video Out	-	1 BNC Out	1 BNC Out	
	Audio In / Out	1 In / -	1 In / 1 Out	1 In / 1 Out	
	Alarm In / Out	No	2 In / 1 Out	2 In / 1 Out	
	Storage	Micro SD (Up to 128 GB)	Micro SD (Up to 128 GB)	Micro SD (Up to 128 GB)	
Network	Ethernet	RJ-45 10/100BASE-T	RJ-45 10/100BASE-T	RJ-45 10/100BASE-T	
	Security	Password protection, IP filter	Password protection, IP filter	Password protection, IP filter	
	Open Protocol	ONVIF (Profile S)	ONVIF (Profile S)	ONVIF (Profile S)	
	Protocol	IPv4 / IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE	
	Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+	
	Video Management Software	Mobile App (iPhone, iPad, Android)	Mobile App (iPhone, iPad, Android)	Mobile App (iPhone, iPad, Android)	
	Max. Connections	4 Level / 8 Users	4 Level / 8 Users	4 Level / 8 Users	
	Power Source	DC12V, POE	DC12V, AC24V, POE	DC12V, AC24V, POE	
General	Max. Power Consumption	4.7W	11W	11W	
	Max. Input Current	360mA (DC 12V), 120mA (PoE)	810mA (AC24V), 880mA (DC12V), 230mA (PoE)	810mA (AC24V), 880mA (DC12V), 230mA (PoE)	
	Operating Temperature / Humidity	-30°C~60°C / 0% ~ 95%RH	-30°C~60°C / 0% ~ 95%RH	-30°C~60°C / 0% ~ 95%RH	
	Standard Approvals	KC, LVD, CE	CCC, Police (China), KC, LVD, CE	CCC, Police (China), KC, LVD, CE	
	Language	Korean, Chinese, Japanese, English, Turkish, Spanish	Korean, Chinese, Japanese, English, Turkish, Spanish	Korean, Chinese, Japanese, English, Turkish, Spanish	
	Color / Material	White / Diecasting	White / Diecasting	White / Diecasting	
	Ingress Protection	IK10, IP66	IK10, IP66	IK10, IP66	
	3-Axis	Manual	Manual	Manual	
	Dimension (Ø x H)	120.4mm x 90mm	150mm x 122mm	150mm x 122mm	
	Weight	0.48 kg	0.96kg (Camera Only)	0.96kg (Camera Only)	

※ Exact products and specifications shown may vary by geographic region and are subject to change without notice. Actual products may differ from the images appearing in the catalog.